

MAXIMUM SLABS

BY SAMMY'S DESIGNER FLOORING



| TECHNICAL SPECIFICATIONS | | | |
|--------------------------|--|-----------------------|---------------------|
| | Flatness (centre curvature / edge curvature / warpage) | ISO-10545-2 | ±0,5% |
| | Amount of water absorbed, in percentage | ISO-10545-3 | E<0,5% |
| | Breaking strength | ISO-10545-4 | ≥2500 N |
| | Resistance to deep abrasion | ISO-10545-6 | <175mm ³ |
| | Fire Reaction Test | UNE EN 13501-1:2002 | |
| | Frost resistance | ISO-10545-12 | |
| | Release of hazardous substances | Does not release VOCs | |



OSSIDIANA

160x320 glossy SKU#: SLAOSSIDG160320

160x320 honed SKU#: SLAOSSIDH160320

6 mm 1/4" ↑ ↓

6.5 mm 1/4" ↑ ↓

Stock

Custom Order

| Surface | 160x320 63"x126" | 118x278 46"x109" | 118x258 46"x101" | 118x118 46"x46" | 60x118 23"x46" |
|---------|---------------------|---------------------|---------------------|--------------------|-------------------|
| glossy | | | | | |
| honed | | | | | |

*all sizes approximate