



187777 Yang
20.0x20.0 cm./7.9"x7.9" **M923** 8mm

Informacion Técnica / Technical Information

WATER ABSORPTION: E <= 0.5% (GRUPO BIa)

Icon	Test	Norm	Result
	SLIP RESISTANCE	UNE 41901 EX	CLASE 2 / CLASS 2
	SLIP RESISTANCE	DIN 51130:2014	R10
	RESISTANCE TO SURFACE ABRASION	UNE EN ISO 10545-7	CLASE 2 / CLASS 2
	CRAZING RESISTANCE	UNE EN ISO 10545-11	CUMPLE / ACCOMPLISH
	FROST RESISTANCE	UNE EN ISO 10545-12	CUMPLE / ACCOMPLISH
	CHEMICAL RESISTANCE	UNE EN ISO 10545-13	GLA
	FLATNESS	UNE EN ISO 10545-2	± 0,5%
	DIMENSIONS	UNE EN ISO 10545-2	± 0,5%
	WATER ABSORPTION	UNE EN ISO 10545-3	E <= 0.5%
	SCRATCH HARDNESS	EN-101	5
	BREAKING STRENGTH	UNE EN ISO 10545-4:9	>35 N/MM2

Embalaje / Packing

Usos / Uses

							Yang 20.0x20.0												
25	14	11.55	25.46	112	.56	62.72			X	X	X	X	X	X	X	C	X	X	X

Pieza/m2 Piece/sqm
 piezas/caja pieces/box
 kg/caja Kg/box
 libras/caja Lbs/box
 cajas/pallet boxes/pallet
 m2/caja sqm/box
 m2/pallet sqm/pallet

- Interior Indoors
- Exterior Outdoors
- Revestimiento Wall
- Pavimento bajo tránsito zonas secas Floors - Light traffic in dry areas
- Pavimento bajo tránsito zonas húmedas Floors - Light traffic in wet areas
- Pavimento alto tránsito Floors - High traffic
- Pavimento radiante Underfloor Heating installation
- Plato ducha Shower floor
- Piscina Swimming pool
- Alta concentración de vapor (sauna, baño turco, etc) High vapor condensation areas (sauna, Turkish bath...)
- Pared ducha Shower Wall