

TIMELESS WOOD FLOORS

OAK ALTMAN MILL CREEK COLLECTION RECLAIMED LOOK 7.5" WIDE PLANK



PRODUCT SPECIFICATIONS

Other Colours / Species	Folwler, Hopkins, Kenyon, Stratton & Woodson
Species	European White Oak
Finish	Ultra-Matte UV Urethane with Aluminum Oxide
Grade	Character / Knotty
Texture	Reclaimed look - bandsaw marks, natural patina & water marks
Edges	4 Side Micro Bevel
Thickness	5/8"
Plank Width	7.5"
Length	random, 23" to 75"
Carton Size	31.09 sq. ft.
Top Layer	4mm Dry Sawn Lamella
Core	Hardwood Plywood
Profiling	Tongue and Grooved on Four Sides
Warranties	Lifetime Structural and 25 Year Residential Finish when properly maintained per care instructions.
Installation Methods	Glue Down, Nail & Glue or Float Approved for use over hydronic radiant heat systems
Mouldings	Nosing, Reducer, T-Mould & Vents
Certification	FloorScore Certified by SCS Global Services



www.TimelessWoodFloors.ca

All measurements nominal, materials subject to normal variations inherent in natural wood products. Images subject to limitations of reproduction and display on individual devices.

TIMELESS WOOD FLOORS

OAK FOWLER MILL CREEK COLLECTION RECLAIMED LOOK 7.5" WIDE PLANK



PRODUCT SPECIFICATIONS

Other Colours / Species	Altman, Hopkins, Kenyon, Stratton & Woodson
Species	European White Oak
Finish	Ultra-Matte UV Urethane with Aluminum Oxide
Grade	Character / Knotty
Texture	Reclaimed look - bandsaw marks, natural patina & water marks
Edges	4 Side Micro Bevel
Thickness	5/8"
Plank Width	7.5"
Length	random, 23" to 75"
Carton Size	31.09 sq. ft.
Top Layer	4mm Dry Sawn Lamella
Core	Hardwood Plywood
Profiling	Tongue and Grooved on Four Sides
Warranties	Lifetime Structural and 25 Year Residential Finish when properly maintained per care instructions.
Installation Methods	Glue Down, Nail & Glue or Float Approved for use over hydronic radiant heat systems
Mouldings	Nosing, Reducer, T-Mould & Vents
Certification	FloorScore Certified by SCS Global Services



www.TimelessWoodFloors.ca

All measurements nominal, materials subject to normal variations inherent in natural wood products. Images subject to limitations of reproduction and display on individual devices.


TIMELESS WOOD FLOORS

OAK HOPKINS MILL CREEK COLLECTION RECLAIMED LOOK 7.5" WIDE PLANK



PRODUCT SPECIFICATIONS

Other Colours / Species	Altman, Fowler, Kenyon, Stratton & Woodson
Species	European White Oak
Finish	Ultra-Matte UV Urethane with Aluminum Oxide
Grade	Character / Knotty
Texture	Reclaimed look - bandsaw marks, natural patina & water marks
Edges	4 Side Micro Bevel
Thickness	5/8"
Plank Width	7.5"
Length	random, 23" to 75"
Carton Size	31.09 sq. ft.
Top Layer	4mm Dry Sawn Lamella
Core	Hardwood Plywood
Profiling	Tongue and Grooved on Four Sides
Warranties	Lifetime Structural and 25 Year Residential Finish when properly maintained per care instructions.
Installation Methods	Glue Down, Nail & Glue or Float Approved for use over hydronic radiant heat systems
Mouldings	Nosing, Reducer, T-Mould & Vents
Certification	FloorScore Certified by SCS Global Services



CERTIFIED BY
SCS Global Services

www.TimelessWoodFloors.ca

All measurements nominal, materials subject to normal variations inherent in natural wood products. Images subject to limitations of reproduction and display on individual devices.

TIMELESS WOOD FLOORS

OAK KENYON MILL CREEK COLLECTION RECLAIMED LOOK 7.5" WIDE PLANK



PRODUCT SPECIFICATIONS

Other Colours / Species	Altman, Fowler, Hopkins, Stratton & Woodson
Species	European White Oak
Finish	Ultra-Matte UV Urethane with Aluminum Oxide
Grade	Character / Knotty
Texture	Reclaimed look - bandsaw marks, natural patina & water marks
Edges	4 Side Micro Bevel
Thickness	5/8"
Plank Width	7.5"
Length	random, 23" to 75"
Carton Size	31.09 sq. ft.
Top Layer	4mm Dry Sawn Lamella
Core	Hardwood Plywood
Profiling	Tongue and Grooved on Four Sides
Warranties	Lifetime Structural and 25 Year Residential Finish when properly maintained per care instructions.
Installation Methods	Glue Down, Nail & Glue or Float Approved for use over hydronic radiant heat systems
Mouldings	Nosing, Reducer, T-Mould & Vents
Certification	FloorScore Certified by SCS Global Services



www.TimelessWoodFloors.ca

All measurements nominal, materials subject to normal variations inherent in natural wood products. Images subject to limitations of reproduction and display on individual devices.

TIMELESS WOOD FLOORS

OAK STRATTON MILL CREEK COLLECTION RECLAIMED LOOK 7.5" WIDE PLANK



PRODUCT SPECIFICATIONS

Other Colours / Species	Altman, Fowler, Hopkins, Kenyon & Woodson
Species	European White Oak
Finish	Ultra-Matte UV Urethane with Aluminum Oxide
Grade	Character / Knotty
Texture	Reclaimed look - bandsaw marks, natural patina & water marks
Edges	4 Side Micro Bevel
Thickness	5/8"
Plank Width	7.5"
Length	random, 23" to 75"
Carton Size	31.09 sq. ft.
Top Layer	4mm Dry Sawn Lamella
Core	Hardwood Plywood
Profiling	Tongue and Grooved on Four Sides
Warranties	Lifetime Structural and 25 Year Residential Finish when properly maintained per care instructions.
Installation Methods	Glue Down, Nail & Glue or Float Approved for use over hydronic radiant heat systems
Mouldings	Nosing, Reducer, T-Mould & Vents
Certification	FloorScore Certified by SCS Global Services



CERTIFIED BY
SCS Global Services

www.TimelessWoodFloors.ca

All measurements nominal, materials subject to normal variations inherent in natural wood products. Images subject to limitations of reproduction and display on individual devices.

TIMELESS WOOD FLOORS

OAK WOODSON MILL CREEK COLLECTION RECLAIMED LOOK 7.5" WIDE PLANK



PRODUCT SPECIFICATIONS

Other Colours / Species	Altman, Fowler, Hopkins, Kenyon & Stratton
Species	European White Oak
Finish	Ultra-Matte UV Urethane with Aluminum Oxide
Grade	Character / Knotty
Texture	Reclaimed look - bandsaw marks, natural patina & water marks
Edges	4 Side Micro Bevel
Thickness	5/8"
Plank Width	7.5"
Length	random, 23" to 75"
Carton Size	31.09 sq. ft.
Top Layer	4mm Dry Sawn Lamella
Core	Hardwood Plywood
Profiling	Tongue and Grooved on Four Sides
Warranties	Lifetime Structural and 25 Year Residential Finish when properly maintained per care instructions.
Installation Methods	Glue Down, Nail & Glue or Float Approved for use over hydronic radiant heat systems
Mouldings	Nosing, Reducer, T-Mould & Vents
Certification	FloorScore Certified by SCS Global Services



www.TimelessWoodFloors.ca

All measurements nominal, materials subject to normal variations inherent in natural wood products. Images subject to limitations of reproduction and display on individual devices.