



Light

FICHA TÉCNICA

Technical Data Sheet

Cemento en acabado pulido
Polished concrete finish

60 X 120 CM.
24 X 48 IN.

Porcelanato esmaltado. Rectificado.
Glazed porcelain tile. Rectified.



15 Caras
15 Faces



Alto Tráfico
High Traffic



Variación Media
Mod. Variation



Pasta Blanca
White body

Uso Usage



Interior



Baño
Bathroom



Cocina
Kitchen

Porcelanato pulido / Polished porcelain tile

Características técnicas / Technical specifications

	Pasta blanca / White body		
	Separación de boquilla / Grout size	2 mm	
	PEI	4	
	Resistencia química / Chemical resistance	Conforme	ASTM C650
	DCOF / Dynamic Coefficient of Friction	>0.42	ASTM C1028
	Absorción de agua / Water absorption	≤0.5%	ASTM C373
	MOHS	5-8	ASTM C1028
	Resistencia de flexión / Breaking strength	>350 kg	ISO 10545-4
	Shock térmico / Thermal shock resistance	Conforme	ASTM C484
	Resistencia a helada / Frost resistance	Conforme	ASTM C1026
	Resistencia a manchas / Stain resistance	Conforme	ASTM C1378
	Resistencia de abrasión / Abrasion resistance	Conforme	ANSI A137
	Información de Embalaje	PZS-CAJA / PCS-BOX 2	M ² -CAJA / FT ² -BOX 1.44 / 15.50 KG-CAJA / LBS-BOX 29.50 / 65.03