

Corbett



All measurements nominal, materials subject to normal variations inherent in natural wood products.

Images subject to limitations of reproduction and display on individual devices.



Product Details

Species	Oak
Color	Light-Medium
Finish	Matte Aluminum Oxide
Grade	Elite - Minimal Knots
Texture	Wire-brushed
Edges	4 Side Micro Bevel
Thickness	½" (12.7mm)
Width	7 ½" (190.5mm)
Lengths	15-¾" - 74-½" (400mm - 1900mm)
Top Layer	2mm Sliced Wear Layer
Core	Hardwood Plywood
Profiling	Tongue and Grooved on Four Sides

Install Method	Approved for above-, on-, or below-grade applications
Warranty	25 year wear-through warranty on finish
	Lifetime structural warranty
Mouldings	Nosing, Reducer, T-Mould & Vents
Sq.ft./Box	31.07



Dawson



All measurements nominal, materials subject to normal variations inherent in natural wood products.

Images subject to limitations of reproduction and display on individual devices.



Product Details

Species	Oak
Color	Light
Finish	Matte Aluminum Oxide
Grade	Elite - Minimal Knots
Texture	Wire-brushed
Edges	4 Side Micro Bevel
Thickness	½" (12.7mm)
Width	7 ½" (190.5mm)
Lengths	15- ³ / ₄ " - 74- ⁴ / ₅ " (400mm - 1900mm)
Top Layer	2mm Sliced Wear Layer
Core	Hardwood Plywood
Profiling	Tongue and Grooved on Four Sides

Install Method	Approved for above-, on-, or below-grade applications
Warranty	25 year wear-through warranty on finish
	Lifetime structural warranty
Mouldings	Nosing, Reducer, T-Mould & Vents
Sq.ft./Box	31.07



Kendall



All measurements nominal, materials subject to normal variations inherent in natural wood products.

Images subject to limitations of reproduction and display on individual devices.



Product Details

Species	Oak
Color	Medium
Finish	Matte Aluminum Oxide
Grade	Elite - Minimal Knots
Texture	Wire-brushed
Edges	4 Side Micro Bevel
Thickness	½" (12.7mm)
Width	7 ½" (190.5mm)
Lengths	15- ³ / ₄ " - 74- ⁴ / ₅ " (400mm - 1900mm)
Top Layer	2mm Sliced Wear Layer
Core	Hardwood Plywood
Profiling	Tongue and Grooved on Four Sides

Install Method	Approved for above-, on-, or below-grade applications
Warranty	25 year wear-through warranty on finish
	Lifetime structural warranty
Mouldings	Nosing, Reducer, T-Mould & Vents
Sq.ft./Box	31.07



Tavani



All measurements nominal, materials subject to normal variations inherent in natural wood products.

Images subject to limitations of reproduction and display on individual devices.



Product Details

Species	Oak
Species	Odk
Color	Light
Finish	Matte Aluminum Oxide
Grade	Elite - Minimal Knots
Texture	Wire-brushed
Edges	4 Side Micro Bevel
Thickness	½" (12.7mm)
Width	7 ½" (190.5mm)
Lengths	15- ³ / ₄ " - 74- ⁴ / ₅ " (400mm - 1900mm)
Top Layer	2mm Sliced Wear Layer
Core	Hardwood Plywood
Profiling	Tongue and Grooved on Four Sides

Install Method	Approved for above-, on-, or below-grade applications
Warranty	25 year wear-through warranty on finish
	Lifetime structural warranty
Mouldings	Nosing, Reducer, T-Mould & Vents
Sq.ft./Box	31.07