

Canyon Desert



All measurements nominal, materials subject to normal variations inherent in natural wood products.

Images subject to limitations of reproduction and display on individual devices.



Product Details

Species	Oak
Color	Light
Finish	Matte Aluminum Oxide
Grade	Character/Filled Knots
Texture	Wire-brushed
Edges	4 Side Micro Bevel
Thickness	%16" (14.3mm)
Width	7 ½" (190.5mm)
Lengths	24" - 72" (609.6mm - 1828.8mm)
Top Layer	3mm Dry Sawn Wear Layer
Core	Hardwood Plywood
Profiling	Tongue and Grooved on Four Sides

Certifications	FloorScore Certified by SCS Global Services
Install Method	Approved for above-, on-, or below-grade applications
Heat Installations	Approved for glue-down radiant heat applications
Warranty	25 year wear-through warranty on finish
,	Lifetime structural warranty
Mouldings	Nosing, Reducer, T-Mould & Vents
Sq.ft./Box	23.31



Glenmore



All measurements nominal, materials subject to normal variations inherent in natural wood products.

Images subject to limitations of reproduction and display on individual devices.



Product Details

Species	Oak
Color	Medium
Finish	Matte Aluminum Oxide
Grade	Character/Filled Knots
Texture	Wire-brushed
Edges	4 Side Micro Bevel
Thickness	%16" (14.3mm)
Width	7 ½" (190.5mm)
Lengths	24" - 72" (609.6mm - 1828.8mm)
Top Layer	3mm Dry Sawn Wear Layer
Core	Hardwood Plywood
Profiling	Tongue and Grooved on Four Sides

Certifications	FloorScore Certified by SCS Global Services
Install Method	Approved for above-, on-, or below-grade applications
Heat Installations	Approved for glue-down radiant heat applications
Warranty	25 year wear-through warranty on finish
,	Lifetime structural warranty
Mouldings	Nosing, Reducer, T-Mould & Vents
Sq.ft./Box	23.31



McKinley



All measurements nominal, materials subject to normal variations inherent in natural wood products.

Images subject to limitations of reproduction and display on individual devices.



Product Details

Species	Oak
Color	Medium
Finish	Matte Aluminum Oxide
Grade	Character/Filled Knots
Texture	Wire-brushed
Edges	4 Side Micro Bevel
Thickness	⁹ /16" (14mm)
Width	7 ½"
Lengths	24" - 72"
Top Layer	3mm Dry Sawn Wear Layer
Core	Hardwood Plywood
Profiling	Tongue and Grooved on Four Sides

Certifications	FloorScore Certified by SCS Global Services
Install Method	Approved for above-, on-, or below-grade applications
Heat Installations	Approved for glue-down radiant heat applications
Warranty	25 year wear-through warranty on finish
	Lifetime structural warranty
Mouldings	Nosing, Reducer, T-Mould & Vents
Sq.ft./Box	23.31



Naramata



All measurements nominal, materials subject to normal variations inherent in natural wood products.

Images subject to limitations of reproduction and display on individual devices.



Product Details

Species	Oak
Color	Light
Finish	Matte Aluminum Oxide
Grade	Character/Filled Knots
Texture	Wire-brushed
Edges	4 Side Micro Bevel
Thickness	%16" (14.3mm)
Width	7 ½" (190.5mm)
Lengths	24" - 72" (609.6mm - 1828.8mm)
Top Layer	3mm Dry Sawn Wear Layer
Core	Hardwood Plywood
Profiling	Tongue and Grooved on Four Sides

Certifications	FloorScore Certified by SCS Global Services
Install Method	Approved for above-, on-, or below-grade applications
Heat Installations	Approved for glue-down radiant heat applications
Warranty	25 year wear-through warranty on finish
,	Lifetime structural warranty
Mouldings	Nosing, Reducer, T-Mould & Vents
Sq.ft./Box	23.31



Orchard Park



All measurements nominal, materials subject to normal variations inherent in natural wood products.

Images subject to limitations of reproduction and display on individual devices.



Product Details

Species	Oak
Color	Light
Finish	Matte Aluminum Oxide
Grade	Character/Filled Knots
Texture	Wire-brushed
Edges	4 Side Micro Bevel
Thickness	⁹ / ₁₆ " (14.3mm)
Width	7 ½" (190.5mm)
Lengths	24" - 72" (609.6mm - 1828.8mm)
Top Layer	3mm Dry Sawn Wear Layer
Core	Hardwood Plywood
Profiling	Tongue and Grooved on Four Sides

Certifications	FloorScore Certified by SCS Global Services
Install Method	Approved for above-, on-, or below-grade applications
Heat Installations	Approved for glue-down radiant heat applications
Warranty	25 year wear-through warranty on finish
	Lifetime structural warranty
Mouldings	Nosing, Reducer, T-Mould & Vents
Sq.ft./Box	23.31



Skaha



All measurements nominal, materials subject to normal variations inherent in natural wood products.

Images subject to limitations of reproduction and display on individual devices.



Product Details

Species	Oak
Color	Light
Finish	Matte Aluminum Oxide
Grade	Character/Filled Knots
Texture	Wire-brushed
Edges	4 Side Micro Bevel
Thickness	%16" (14.3mm)
Width	7 ½" (190.5mm)
Lengths	24" - 72" (609.6mm - 1828.8mm)
Top Layer	3mm Dry Sawn Wear Layer
Core	Hardwood Plywood
Profiling	Tongue and Grooved on Four Sides

Certifications	FloorScore Certified by SCS Global Services
Install Method	Approved for above-, on-, or below-grade applications
Heat Installations	Approved for glue-down radiant heat applications
Warranty	25 year wear-through warranty on finish
	Lifetime structural warranty
Mouldings	Nosing, Reducer, T-Mould & Vents
Sq.ft./Box	23.31



Sorrento



All measurements nominal, materials subject to normal variations inherent in natural wood products.

Images subject to limitations of reproduction and display on individual devices.



Product Details

Species	Oak
Color	Dark
Finish	Matte Aluminum Oxide
Grade	Character/Filled Knots
Texture	Wire-brushed
Edges	4 Side Micro Bevel
Thickness	⁹ /16" (14mm)
Width	7 ½"
Lengths	24" - 72"
Top Layer	3mm Dry Sawn Wear Layer
Core	Hardwood Plywood
Profiling	Tongue and Grooved on Four Sides

Certifications	FloorScore Certified by SCS Global Services
Install Method	Approved for above-, on-, or below-grade applications
Heat Installations	Approved for glue-down radiant heat applications
Warranty	25 year wear-through warranty on finish
	Lifetime structural warranty
Mouldings	Nosing, Reducer, T-Mould & Vents
Sq.ft./Box	23.31



Trader's Cove



All measurements nominal, materials subject to normal variations inherent in natural wood products.

Images subject to limitations of reproduction and display on individual devices.



Product Details

Species	Oak
Color	Medium
Finish	Matte Aluminum Oxide
Grade	Character/Filled Knots
Texture	Wire-brushed
Edges	4 Side Micro Bevel
Thickness	%16" (14.3mm)
Width	7 ½" (190.5mm)
Lengths	24" - 72" (609.6mm - 1828.8mm)
Top Layer	3mm Dry Sawn Wear Layer
Core	Hardwood Plywood
Profiling	Tongue and Grooved on Four Sides

Certifications	FloorScore Certified by SCS Global Services
Install Method	Approved for above-, on-, or below-grade applications
Heat Installations	Approved for glue-down radiant heat applications
Warranty	25 year wear-through warranty on finish
	Lifetime structural warranty
Mouldings	Nosing, Reducer, T-Mould & Vents
Sq.ft./Box	23.31



Woodsdale



All measurements nominal, materials subject to normal variations inherent in natural wood products.

Images subject to limitations of reproduction and display on individual devices.



Product Details

Species	Oak
Color	Medium
Finish	Matte Aluminum Oxide
Grade	Character/Filled Knots
Texture	Wire-brushed
Edges	4 Side Micro Bevel
Thickness	⁹ / ₁₆ " (14mm)
Width	7 ½"
Lengths	24" - 72"
Top Layer	3mm Dry Sawn Wear Layer
Core	Hardwood Plywood
Profiling	Tongue and Grooved on Four Sides

Certifications	FloorScore Certified by SCS Global Services
Install Method	Approved for above-, on-, or below-grade applications
Heat Installations	Approved for glue-down radiant heat applications
Warranty	25 year wear-through warranty on finish
	Lifetime structural warranty
Mouldings	Nosing, Reducer, T-Mould & Vents
Sq.ft./Box	23.31