

Brazza



All measurements nominal, materials subject to normal variations inherent in natural wood products.

Images subject to limitations of reproduction and display on individual devices.



Product Details

Species	White Oak
Colour	Light
Finish	Ultra-Matte UV Urethane with Aluminum Oxide
Grade	Elite/Minimal Knots
Texture	Wire-brushed
Edges	4 Side Micro Bevel
Thickness	½" (14.29mm)
Width	7-½" (177.8mm)
Lengths	19" - 75" Random Lengths (482.6mm - 1905mm)
Top Layer	2mm
Core	Hardwood Plywood
Profiling	Tongue and Grooved on Four Sides

Certifications	FloorScore Certified by SCS Global Services
Install Method	Approved for above-, on-, or below-grade applications
Heat Installations	Approved for glue-down radiant heat applications
Warranty	25 year wear-through warranty on finish
	Lifetime structural warranty
Mouldings	Nosing, Reducer, T-Mould & Vents
Sq.ft./Box	31.11



Corsi



All measurements nominal, materials subject to normal variations inherent in natural wood products.

Images subject to limitations of reproduction and display on individual devices.



Product Details

Species	White Oak
Colour	Medium
Finish	Ultra-Matte UV Urethane with Aluminum Oxide
Grade	Elite/Minimal Knots
Texture	Wire-brushed
Edges	4 Side Micro Bevel
Thickness	½" (14.29mm)
Width	7-½" (177.8mm)
Lengths	19" - 75" Random Lengths (482.6mm - 1905mm)
Top Layer	2mm
Core	Hardwood Plywood
Profiling	Tongue and Grooved on Four Sides

Certifications	FloorScore Certified by SCS Global Services
Install Method	Approved for above-, on-, or below-grade applications
Heat Installations	Approved for glue-down radiant heat applications
Warranty	25 year wear-through warranty on finish
	Lifetime structural warranty
Mouldings	Nosing, Reducer, T-Mould & Vents
Sq.ft./Box	31.11



Delfini



All measurements nominal, materials subject to normal variations inherent in natural wood products.

Images subject to limitations of reproduction and display on individual devices.



Product Details

Species	White Oak
Colour	Light
Finish	Ultra-Matte UV Urethane with Aluminum Oxide
Grade	Elite/Minimal Knots
Texture	Wire-brushed
Edges	4 Side Micro Bevel
Thickness	½" (14.29mm)
Width	7-½" (177.8mm)
Lengths	19" - 75" Random Lengths (482.6mm - 1905mm)
Top Layer	2mm
Core	Hardwood Plywood
Profiling	Tongue and Grooved on Four Sides

Certifications	FloorScore Certified by SCS Global Services
Install Method	Approved for above-, on-, or below-grade applications
Heat Installations	Approved for glue-down radiant heat applications
Warranty	25 year wear-through warranty on finish
	Lifetime structural warranty
Mouldings	Nosing, Reducer, T-Mould & Vents
Sq.ft./Box	31.11



Galvani



All measurements nominal, materials subject to normal variations inherent in natural wood products.

Images subject to limitations of reproduction and display on individual devices.



Product Details

Chasias	\\/\site Oals
Species	White Oak
Colour	Medium
Finish	Ultra-Matte UV Urethane with Aluminum Oxide
Grade	Elite/Minimal Knots
Texture	Wire-brushed
Edges	4 Side Micro Bevel
Thickness	½" (14.29mm)
Width	7-½" (177.8mm)
Lengths	19" - 75" Random Lengths (482.6mm - 1905mm)
Top Layer	2mm
Core	Hardwood Plywood
Profiling	Tongue and Grooved on Four Sides

Certifications	FloorScore Certified by SCS Global Services
Install Method	Approved for above-, on-, or below-grade applications
Heat Installations	Approved for glue-down radiant heat applications
Warranty	25 year wear-through warranty on finish
	Lifetime structural warranty
Mouldings	Nosing, Reducer, T-Mould & Vents
Sq.ft./Box	31.11



Genova



All measurements nominal, materials subject to normal variations inherent in natural wood products.

Images subject to limitations of reproduction and display on individual devices.



Product Details

Species	White Oak
Colour	Light
Finish	Ultra-Matte UV Urethane with Aluminum Oxide
Grade	Elite/Minimal Knots
Texture	Wire-brushed
Edges	4 Side Micro Bevel
Thickness	½" (14.29mm)
Width	7-½" (177.8mm)
Lengths	19" - 75" Random Lengths (482.6mm - 1905mm)
Top Layer	2mm
Core	Hardwood Plywood
Profiling	Tongue and Grooved on Four Sides

Certifications	FloorScore Certified by SCS Global Services
Install Method	Approved for above-, on-, or below-grade applications
Heat Installations	Approved for glue-down radiant heat applications
Warranty	25 year wear-through warranty on finish
	Lifetime structural warranty
Mouldings	Nosing, Reducer, T-Mould & Vents
Sq.ft./Box	31.11



Pavone



All measurements nominal, materials subject to normal variations inherent in natural wood products.

Images subject to limitations of reproduction and display on individual devices.



Product Details

Species	White Oak
Colour	Medium
Finish	Ultra-Matte UV Urethane with Aluminum Oxide
Grade	Elite/Minimal Knots
Texture	Wire-brushed
Edges	4 Side Micro Bevel
Thickness	½" (14.29mm)
Width	7-½" (177.8mm)
Lengths	19" - 75" Random Lengths (482.6mm - 1905mm)
Top Layer	2mm
Core	Hardwood Plywood
Profiling	Tongue and Grooved on Four Sides

Certifications	FloorScore Certified by SCS Global Services
Install Method	Approved for above-, on-, or below-grade applications
Heat Installations	Approved for glue-down radiant heat applications
Warranty	25 year wear-through warranty on finish
	Lifetime structural warranty
Mouldings	Nosing, Reducer, T-Mould & Vents
Sq.ft./Box	31.11



Renzi



All measurements nominal, materials subject to normal variations inherent in natural wood products.

Images subject to limitations of reproduction and display on individual devices.



Product Details

Species	White Oak
Colour	Light
Finish	Ultra-Matte UV Urethane with Aluminum Oxide
Grade	Elite/Minimal Knots
Texture	Wire-brushed
Edges	4 Side Micro Bevel
Thickness	½" (14.29mm)
Width	7-½" (177.8mm)
Lengths	19" - 75" Random Lengths (482.6mm - 1905mm)
Top Layer	2mm
Core	Hardwood Plywood
Profiling	Tongue and Grooved on Four Sides

Certifications	FloorScore Certified by SCS Global Services
Install Method	Approved for above-, on-, or below-grade applications
Heat Installations	Approved for glue-down radiant heat applications
Warranty	25 year wear-through warranty on finish
	Lifetime structural warranty
Mouldings	Nosing, Reducer, T-Mould & Vents
Sq.ft./Box	31.11