

S M A L L

the big world of the small size



WHITE

9 mm



12,4x10,7
5"x41/4 "
180048 Bright



10x10
4"x4"
180068 Bright



6,5x20
21/2 "x8"
180008 Bright



5,1x16,1
2"x61/3 "
180028 Bright



Jolly 1,2x20
1/2 "x8"
180088 Bright



Pencil bullnose 3x20
11/4 "x8"
180108 Bright

BEIGE

9 mm



12,4x10,7
5"x41/4 "
180050 Bright



10x10
4"x4"
180070 Bright



6,5x20
21/2 "x8"
180010 Bright



5,1x16,1
2"x61/3 "
180030 Bright



Jolly 1,2x20
1/2 "x8"
180090 Bright



Pencil bullnose 3x20
11/4 "x8"
180110 Bright

BLACK

9 mm



12,4x10,7
5"x41/4 "
180041 Bright



10x10
4"x4"
180061 Bright



6,5x20
21/2 "x8"
180001 Bright



5,1x16,1
2"x61/3 "
180021 Bright



Jolly 1,2x20
1/2 "x8"
180081 Bright



Pencil bullnose 3x20
11/4 "x8"
180101 Bright

SAGE

9 mm



12,4x10,7
5"x41/4 "
180046 Bright



10x10
4"x4"
180066 Bright



6,5x20
21/2 "x8"
180006 Bright



5,1x16,1
2"x61/3 "
180026 Bright



Jolly 1,2x20
1/2 "x8"
180086 Bright



Pencil bullnose 3x20
11/4 "x8"
180106 Bright

CARATTERISTICHE TECNICHE

Technical features.
Caracteristiques techniques.
Technische eigenschaften.

PASTA BIANCA - RIVESTIMENTO

White body - wall tiles
Pâte blanche - pour revêtement
Weißscherbíg - Für wanderbelag

UNI EN 14411 - ISO 13006 B III - GL -

	CARATTERISTICA EIGENSCHAFT DIMENSIONE LATI DIMENSIONS - LONGUEUR ET LARGEUR LÄNGE UND BREITE	SPECIFICATION CARACTERISTIQUE LENGHT AND WIDTH	METODO DI PROVA TEST METHODS METHODE D'ESSAI TESTVERFAHREN	VALORE PRESCRITTO FIXED VALUE VALEUR PRESCRITE VORGESCHRIEBENER WERT	UNITÀ DI MISURA UNIT OF MESUREMENT UNITÉ DE MESURE MASSEINHEIT	
	RETTILINEITÀ DEI LATI SIDES' STRAIGHTNESS RECTITUDE DES CÔTES GERADLINIGKEIT DER KANTEN ORTAGONALITÀ DEI LATI SIDES' ORTOGONALITY OCTOGONALITÉ DES CÔTES RECHTWINKLIGKEIT DER KANTEN PLANARITÀ FLATNESS PLANEITUDE EBENFLÄCHIGKEIT SPESSORE THICKNESS ÉPAISSEUR STÄRKE ASSORBIMENTO D'ACQUA WATER ABSORPTION ABSORPTION D'EAU WASSERAUFNAHME SFORZO DI ROTTURA MODULUS OF RUPTURE CHARGE DE RUPTURE BRUCHLAST MODULO DI ROTTURA MODULUS OF RUPTURE		UNI EN ISO 10545-2	± 0,5 ± 0,3 ± 0,5 ± 0,5 ± 10	% % % % %	Civilization of Beauty
	COEFFICIENTE DI DILATAZIONE TERMICA LINEARE THERMAL EXPANSION COEFFICIENT COEFFICIENT DE DILATATION THERMIQUE LINEAIRE WARMEAUDEHNUNGSKOEFFIZIENT RESISTENZA AGLI SBALZI TERMICI THERMAL SHOCK RESISTANCE RESISTANCE AUX ÉCARTS DE TEMPERATURE TEMPERATURWECHSELBESTÄNDIGKEIT		UNI EN ISO 10545-4	≥ 600 SE SPESS ≥ 7,5 mm. ≥ 200 SE SPESS < 7,5 mm. ≥ 15 SE SPESS < 7,5 mm. ≥ 12 SE SPESS ≥ 7,5 mm.	N N /mm2	CONFORME . COMPLIANT CONFORME . ERFÜLLT CONFORME . COMPLIANT CONFORME . ERFÜLLT
	RESISTENZA AL CAVILLO CRAZING RESISTANT RÉSISTENCE AUX TRÉSSAILLURES HAARRISSE		UNI EN ISO 10545-8	METODO DISPONIBILE AVAILABLE ON REQUEST METHODE DISPONIBLE VERFÜGBARES VERFAHREN	* MK (-1)	7,00
	RESISTENZA ALLE MACCHIE STAIN RESISTANCE RÉSISTANCE AUX TACHES FLECKBESTÄNDIGKEIT		UNI EN ISO 10545-9	METODO DISPONIBILE AVAILABLE ON REQUEST METHODE DISPONIBLE VERFÜGBARES VERFAHREN		RESISTENTI . RESISTANT RÉSISTANTS . WIDERSTANDSFAHIG
	RESISTENZA ALL'ATTACCO CHIMICO CHEMICAL RESISTANCE RÉSISTENCE AUX PRODUITS CHIMIQUES BESTÄNDIGKEIT GEGEN CHEMIKALIEN		UNI EN ISO 10545-11	RICHIESTA . ALWAYS TESTED EXIGÉE . NOTWENDIG		RESISTENTI . RESISTANT RÉSISTANTS . WIDERSTANDSFAHIG
	RESISTENZA AGLI ACIDI E ALLE BASI A BASSA CONCENTRAZIONE RESISTANT TO ACID AND LOW CONCENTRATION BASES RÉSISTANCE AUX ACIDES ET AUX BASES À FAIBLE		UNI EN ISO 10545-14	3 MIN		4-5
	CONCENTRAZIONE WIDERSTANDSFAHIG GEGENUBER NIEDRIG SAUREN UND LAUGEN RESISTENZA ALL'ABRASIONE RESISTANCE TO ABRASION RÉSISTENCE À L'ABRASION BESTÄNDIGKEIT GEGEN OBERFLÄCHENVERSCHLEISS		UNI EN ISO 10545-13	GBMIN METODO DISPONIBILE AVAILABLE ON REQUEST METHODE DISPONIBLE VERFÜGBARES VERFAHREN		CONFORME . COMPLIANT CONFORME . ERFÜLLT ≥ GLB
			UNI EN ISO 10545-7	CLASSE 1-5 CLASS 1-5 CLASSE 1-5 KLASSE 1-5		2-5

CERTIFICAZIONI DI SISTEMA

System certification.
Certifications du système.
Systemzertifikationen.

IMBALLI

	PCS/BOX	MQ/BOX	KG/BOX	BOX /PAL	MQ/PAL	KG/PAL	PACKING	PACKING SIZE
9								
12,4 x 10,7 10 x 10 6,5	5	0,5	7,6	84	42	665	EPA	80 x
x 20 5,1 x 16,1 JOLLY	0	0	8	120	60	887	L	120 80
1,2 x 20 PENCIL	5	0,5	7,2	120	60	950	EPA	x 120
BULLNOSE 3 x 20	0	0	3	120	64,80	974	L	80 x
	3	0,5	7,7	-	-	-	EPA	120 80
	8	0	5	-	-	-	L	x 120
	6	0,5	7,9				EPA	80 x
	6	4	5				L	120 80
	6	0,1	2,6				EPA	x 120
	6	6	4				L	
	1	0,0	1,7				EPA	
	5	9	3				L	

CERTIFICAZIONI DI PRODOTTO

Product certification.
Certification de produit.
Produkt Zertifizierungen.

